




















































MECHANICAL SYMBOLS LIST	
NOTE: NOT ALL SYMBOLS MAY BE USED.	
SYMBOL	DESCRIPTION
	HUMIDISTAT WITH ADJUSTABLE CONTROL
	THERMOSTAT WITH ADJUSTABLE CONTROL
	HUMIDITY SENSOR
	TEMPERATURE SENSOR
	HYDROGEN SENSOR
	CARBON DIOXIDE SENSOR
	CARBON MONOXIDE SENSOR
	NITROGEN DIOXIDE SENSOR
	OCCUPANCY SENSOR
	KEYNOTE (SEE LEGEND ON SHEET)
	REVISION TRIANGLE
	AIRFLOW ARROW
	FLOW ARROW
	CONNECT TO EXISTING
	END OF DEMOLITION
	PIPE CAPPED
	PIPE DROP
	PIPE RISE
	PIPE TEE DOWN
	PIPE TEE UP
	PIPE REDUCER
	PIPE UNION
	PIPE GUIDES OR SLEEVES
	PIPE ANCHOR
	FLEXIBLE PIPE CONNECTION
	GENERAL SERVICE VALVE (SEE SPECIFICATIONS FOR VALVE TYPE PER APPLICATION)
	CHECK VALVE (ARROW INDICATES DIRECTION OF FLOW)
	MANUAL BALANCING VALVE
	AUTOMATIC BALANCING VALVE
	TWO-WAY CONTROL VALVE
	THREE-WAY CONTROL VALVE
	TWO-WAY PRESSURE INDEPENDENT CONTROL VALVE
	PRESSURE REDUCING VALVE
	STEAM PRESSURE REGULATING VALVE
	RELIEF VALVE
	DRAIN VALVE WITH THREADED HOSE CONNECTION
	REDUCED PRESSURE BACKFLOW PREVENTER
	PRESSURE GAUGE WITH STOPCOCK
	STRAINER WITH BLOW DOWN VALVE
	AUTOMATIC AIR VENT
	MANUAL AIR VENT
	TEMPERATURE/PRESSURE TEST PLUG (PET'S PLUG)
	SIGHT FLOW INDICATOR
	STEAM TRAP
	CLEAN OUT
	FLOW METER
	THERMOMETER
	PITCH DOWN IN DIRECTION OF ARROW





















WALL RATING LEGEND	
	FIRE RESISTIVE RATED WALLS, 1 HOUR
	FIRE RESISTIVE RATED WALLS, 2 HOUR
	FIRE RATED, SMOKE BARRIER WALLS, 1 HOUR
	FIRE RATED, SMOKE BARRIER WALLS, 2 HOUR

MECHANICAL SYMBOLS LIST CONT.			
NOTE: NOT ALL SYMBOLS MAY BE USED.			
SYMBOL		DESCRIPTION	
		TERMINAL BOXES	
		VAV TERMINAL BOX (WITH REHEAT)	
		VAV TERMINAL BOX (NO REHEAT)	
		TERMINAL BOX NOTES	
		1. IF MIN COOLING CFM IS NOT SHOWN ON PLANS, THEN MIN COOLING CFM IS EQUAL TO 65% OF MAX COOLING CFM.	
		2. HEATING CFM IS EQUAL TO MIN COOLING CFM.	
		DUCTWORK PLANS	
		TAG _____ MAX COOLING CFM / MIN COOLING CFM	
		PIPING PLANS	
		TAG _____	
TAG EXAMPLES:		DUCTWORK PLANS TB1 500/200 TB1 500	PIPING PLANS TB1
		SUPPLY AND OUTDOOR AIR	
		RECTANGULAR DUCT ELBOW UP	
		OVAL DUCT ELBOW UP	
		RETURN, RELIEF, AND EXHAUST AIR	
		RECTANGULAR DUCT ELBOW UP	
		OVAL DUCT ELBOW UP	
		SUPPLY AND OUTDOOR AIR	
		RECTANGULAR DUCT ELBOW DOWN	
		OVAL DUCT ELBOW DOWN	
		RETURN, RELIEF, AND EXHAUST AIR	
		RECTANGULAR DUCT ELBOW DOWN	
		OVAL DUCT ELBOW DOWN	
		RETURN, RELIEF, AND EXHAUST AIR	
		RECTANGULAR DUCT ELBOW DOWN	
		OVAL DUCT ELBOW DOWN	
		RETURN, RELIEF, AND EXHAUST AIR	
		RECTANGULAR DUCT ELBOW DOWN	
		OVAL DUCT ELBOW DOWN	
		RETURN, RELIEF, AND EXHAUST AIR	
		RECTANGULAR DUCT ELBOW DOWN	
		OVAL DUCT ELBOW DOWN	
		RETURN, RELIEF, AND EXHAUST AIR	
		RECTANGULAR DUCT ELBOW DOWN	
		OVAL DUCT ELBOW DOWN	
		RETURN, RELIEF, AND EXHAUST AIR	
		RECTANGULAR DUCT ELBOW DOWN	
		OVAL DUCT ELBOW DOWN	
		RETURN, RELIEF, AND EXHAUST AIR	
		RECTANGULAR DUCT ELBOW DOWN	
		OVAL DUCT ELBOW DOWN	
		RETURN, RELIEF, AND EXHAUST AIR	
		RECTANGULAR DUCT ELBOW DOWN	
		OVAL DUCT ELBOW DOWN	
		RETURN, RELIEF, AND EXHAUST AIR	
		RECTANGULAR DUCT ELBOW DOWN	
		OVAL DUCT ELBOW DOWN	
		RETURN, RELIEF, AND EXHAUST AIR	
		RECTANGULAR DUCT ELBOW DOWN	
		OVAL DUCT ELBOW DOWN	
		RETURN, RELIEF, AND EXHAUST AIR	
		RECTANGULAR DUCT ELBOW DOWN	
		OVAL DUCT ELBOW DOWN	
		RETURN, RELIEF, AND EXHAUST AIR	
		RECTANGULAR DUCT ELBOW DOWN	
		OVAL DUCT ELBOW DOWN	
		RETURN, RELIEF, AND EXHAUST AIR	
		RECTANGULAR DUCT ELBOW DOWN	
		OVAL DUCT ELBOW DOWN	
		RETURN, RELIEF, AND EXHAUST AIR	
		RECTANGULAR DUCT ELBOW DOWN	
		OVAL DUCT ELBOW DOWN	
		RETURN, RELIEF, AND EXHAUST AIR	
		RECTANGULAR DUCT ELBOW DOWN	
		OVAL DUCT ELBOW DOWN	
		RETURN, RELIEF, AND EXHAUST AIR	
		RECTANGULAR DUCT ELBOW DOWN	
		OVAL DUCT ELBOW DOWN	
		RETURN, RELIEF, AND EXHAUST AIR	
		RECTANGULAR DUCT ELBOW DOWN	
		OVAL DUCT ELBOW DOWN	
		RETURN, RELIEF, AND EXHAUST AIR	
		RECTANGULAR DUCT ELBOW DOWN	
		OVAL DUCT ELBOW DOWN	
		RETURN, RELIEF, AND EXHAUST AIR	
		RECTANGULAR DUCT ELBOW DOWN	
		OVAL DUCT ELBOW DOWN	
		RETURN, RELIEF, AND EXHAUST AIR	
		RECTANGULAR DUCT ELBOW DOWN	
		OVAL DUCT ELBOW DOWN	
		RETURN, RELIEF, AND EXHAUST AIR	
		RECTANGULAR DUCT ELBOW DOWN	
		OVAL DUCT ELBOW DOWN	
		RETURN, RELIEF, AND EXHAUST AIR	
		RECTANGULAR DUCT ELBOW DOWN	
		OVAL DUCT ELBOW DOWN	
		RETURN, RELIEF, AND EXHAUST AIR	
		RECTANGULAR DUCT ELBOW DOWN	
		OVAL DUCT ELBOW DOWN	
		RETURN, RELIEF, AND EXHAUST AIR	
		RECTANGULAR DUCT ELBOW DOWN	
		OVAL DUCT ELBOW DOWN	
		RETURN, RELIEF, AND EXHAUST AIR	
		RECTANGULAR DUCT ELBOW DOWN	
		OVAL DUCT ELBOW DOWN	
		RETURN, RELIEF, AND EXHAUST AIR	
		RECTANGULAR DUCT ELBOW DOWN	
		OVAL DUCT ELBOW DOWN	
		RETURN, RELIEF, AND EXHAUST AIR	
		RECTANGULAR DUCT ELBOW DOWN	
		OVAL DUCT ELBOW DOWN	

MECHANICAL ABBREVIATIONS	
NOTE: NOT ALL ABBREVIATIONS MAY BE USED.	
ABBREVIATION	DESCRIPTION
(D)	EXISTING TO BE DEMOLISHED
(E)	EXISTING TO REMAIN
(F)	FUTURE
AFF	ABOVE FINISHED FLOOR
AMB	AMBIENT
APD	AIR PRESSURE DROP
AVG	AVERAGE OR AVERAGING
BAS	BUILDING AUTOMATION SYSTEM
BFP	BACKFLOW PREVENTOR
BHP	BRAKE HORSEPOWER
BLDG	BUILDING
BOB	BOTTOM OF BEAM
BOD	BOTTOM OF DUCT
BOP	BOTTOM OF PIPE
BOS	BOTTOM OF STRUCTURE
BTUH	BRITISH THERMAL UNITS PER HOUR
CFM	CUBIC FEET PER MINUTE
CL	CENTER LINE
CO	CLEAN OUT
COMPR	COMPRESSOR
COP	COEFFICIENT OF PERFORMANCE
CV	CONSTANT VOLUME
DB	DRY BULB
DDC	DIRECT DIGITAL CONTROLS
DN	DOWN
EAT	ENTERING AIR TEMPERATURE
ECM	ELECTRONICALLY COMMUTATED MOTORS
EER	ENERGY EFFICIENCY RATIO
EFF	EFFICIENCY
EG	ETHYLENE GLYCOL
ESP	EXTERNAL STATIC PRESSURE
EWT	ENTERING WATER TEMPERATURE
FLA	FULL LOAD AMPS
FPI	FINS PER INCH
PPM	FEET PER MINUTE
FPS	FEET PER SECOND
FT	FEET
GAL	GALLONS
GPM	GALLONS PER MINUTE
HD	HEAD
HP	HORSEPOWER
ID	INNER DIAMETER
IPLV	INTEGRATED PART LOAD VALUE
KW	KILOWATTS
LAT	LEAVING AIR TEMPERATURE
LWT	LEAVING WATER TEMPERATURE
MBH	THOUSAND BTUH
MCA	MINIMUM CIRCUIT AMPACITY
MFR	MANUFACTURER
MOCP	MAXIMUM OVERCURRENT PROTECTION
N/A	NOT APPLICABLE
NC	NORMALLY CLOSED
NO	NORMALLY OPEN
NPLV	NON-STANDARD PART LOAD VALUE
NPSH	NET POSITIVE SUCTION HEAD
NTS	NOT TO SCALE
OD	OUTSIDE DIAMETER
PD	PRESSURE DROP
PG	PROPYLENE GLYCOL
PPH	POUNDS PER HOUR
PPM	PARTS PER MILLION
PRV	PRESSURE REDUCING VALVE
PSI	POUNDS PER SQUARE INCH
REFRIG	REFRIGERANT
RH	RELATIVE HUMIDITY
RPM	REVOLUTIONS PER MINUTE
SEER	SEASONAL ENERGY EFFICIENCY RATIO
SP	STATIC PRESSURE
TSP	TOTAL STATIC PRESSURE
TYP	TYPICAL
UNO	UNLESS NOTED OTHERWISE
VAV	VARIABLE AIR VOLUME
VFD	VARIABLE FREQUENCY DRIVE
VOC	VOLATILE ORGANIC COMPOUNDS
VRF	VARIABLE REFRIGERANT FLOW
W	WATTS
WB	WET BULB
WG	WATER GAUGE
WPD	WATER PRESSURE DROP


MECHANICAL SYSTEM TYPES AND ABBREVIATIONS	
NOTE: NOT ALL ABBREVIATIONS MAY BE USED.	
ABBREVIATION	DESCRIPTION
CHR	CHILLED WATER RETURN
CHS	CHILLED WATER SUPPLY
CWR	CONDENSER WATER RETURN
CWS	CONDENSER WATER SUPPLY
D	DRAIN
EA	EXHAUST AIR
GR	GEO THERMAL RETURN
GS	GEO THERMAL SUPPLY
HR	HEAT PUMP RETURN
HS	HEAT PUMP SUPPLY
HWR	HEATING HOT WATER RETURN
HWS	HEATING HOT WATER SUPPLY
MW	MAKEUP WATER - GENERIC
OA	OUTDOOR AIR
PC	PUMPED CONDENSATE
RA	RETURN AIR
REF	REFRIGERANT
REL	RELIEF AIR
SA	SUPPLY AIR
V	VENT


MECHANICAL STEAM SYSTEM TYPES AND ABBREVIATIONS	
NOTE: NOT ALL ABBREVIATIONS MAY BE USED.	
ABBREVIATION	DESCRIPTION
BBD	STEAM BOILER BOTTOM BLOWDOWN
BD	STEAM BOILER BLOWDOWN
BFW	STEAM BOILER FEEDWATER
CBQ	STEAM BOILER CONTINUOUS BLOWDOWN
CF	CHEMICAL FEED
CLPS(Psi)	CLEAN LOW PRESSURE STEAM (Psi)
HPC	HIGH PRESSURE STEAM CONDENSATE
HPSP(Psi)	HIGH PRESSURE STEAM (Psi) = 60 PSI AND ABOVE
LPC	LOW PRESSURE STEAM CONDENSATE
LPS(Psi)	LOW PRESSURE STEAM (Psi) = 15 PSI AND BELOW
MPC	MEDIUM PRESSURE STEAM CONDENSATE
MPS(Psi)	MEDIUM PRESSURE STEAM (Psi) = 16 PSI - 59 PSI
PSC	PUMPED STEAM CONDENSATE
SV	STEAM VENT
VSC	VACUUM STEAM CONDENSATE

MECHANICAL CONTROLS SYMBOLS LIST	
NOTE: NOT ALL SYMBOLS MAY BE USED.	
SYMBOL	DESCRIPTION
	AIR FLOW MEASURING DEVICE
	AIR SWITCH
	CONDUCTIVITY TRANSMITTER
	CURRENT SENSOR
	DIFFERENTIAL PRESSURE TRANSMITTER
	ELECTRONIC PNEUMATIC TRANSDUCER
	END SWITCH
	FLOW METER
	HAND-OFF-AUTO SWITCH
	LEVEL TRANSMITTER
	METER
	PH TRANSMITTER
	PRESSURE SWITCH
	PRESSURE TRANSMITTER
	SMOKE DETECTOR
	STARTER
	TEMPERATURE SWITCH
	VARIABLE FREQUENCY DRIVE
	VIBRATION TRANSMITTER
	WATER FLOW SWITCH

MECHANICAL SHEET INDEX	
SHEET NUMBER	SHEET TITLE
M001	GENERAL INFORMATION - HVAC
M301	HVAC ENLARGED PLAN - NORTH MER DEMO
M302	HVAC ENLARGED PLANS - NORTH MER NEW WORK
M701	HVAC SCHEDULES & DETAILS

[illegible]





Greater Columbus Convention Center North Facility Chiller Replacement - 2023-5

CLIENT

**FRANKLIN COUNTY
CONVENTION FACILITIES
AUTHORITY**

400 North High Street, 4th Floor
Columbus, Ohio 43215

CONSULTANTS

REMARKS:

1. CHILLERS HAVE BEEN PRE-PURCHASED BY OWNER AND ARE SCHEDULED FOR REFERENCE ONLY.
2. NEW CHILLERS TO FOLLOW EXISTING SEQUENCE OF OPERATION.

REMARKS:

1. PUMPS TO BE PROVIDED WITH NEW VFDS INSTALLED IN SIMILAR LOCATION AS VFDS BEING REMOVED
2. NEW PUMPS TO FOLLOW EXISTING SEQUENCE OF OPERATION.



KEYPLAN

[illegible]

OCCC23

SHEET NUMBER

M701

ELECTRICAL GENERAL NOTES:

- A. EACH CONTRACTOR, PROPOSER, SUPPLIER AND/OR MANUFACTURER SHALL REFER TO ALL DOCUMENTS PERTAINING TO THIS PROJECT AND COORDINATE ACCORDINGLY SO AS TO ENSURE ADEQUACY OF FIT, COMPLIANCE WITH SPECIFICATIONS, PROPER VOLTAGE AND CURRENT CHARACTERISTICS TO AVOID CONFLICT WITH ANY OTHER BUILDINGS SYSTEMS. VERIFY SAME WITH SHOP DRAWINGS.
- B. ADDITIONAL ELECTRICAL REQUIREMENTS MAY BE SHOWN ON PLANS FROM OTHER DISCIPLINES IN THIS SET. IT IS THE CONTRACTOR'S RESPONSIBILITY TO REVIEW ALL PLANS AND SPECIFICATIONS FOR A COMPLETE UNDERSTANDING OF THE PROJECT REQUIREMENTS.
- C. WORK SHALL BE IN ACCORDANCE WITH THE LATEST EDITION OF ALL LOCAL, STATE, AND NATIONAL CODES, INCLUDING BUT NOT LIMITED TO NFPA 70 (NEC), NFPA 72, INTERNATIONAL BUILDING CODES, ETC.
- D. CONTRACTOR SHALL FOLLOW LOW SEISMIC RESTRAINT AND DESIGN REQUIREMENTS CONTAINED IN LATEST ADOPTED STATE AND INTERNATIONAL BUILDING CODES, WITH ALL AMENDMENTS AS ADOPTED BY THE CURRENT LEGISLATION. REFER TO ELECTRICAL AND STRUCTURAL SPECIFICATIONS FOR ADDITIONAL INFORMATION.
- E. ALL OFFSETS, TURNS, FITTINGS, TRIM, DETAIL, ETC. MAY NOT BE INDICATED, BUT SHALL BE PROVIDED AS REQUIRED. ADDITIONAL ALLOWANCES SHALL BE INCLUDED FOR SAME AT EACH PROPOSER'S DISCRETION.
- F. INSTALL NO PIPING, CONDUIT, DUCTWORK, ETC. IN A LOCATION OR IN A MANNER WHICH WILL ALLOW FREEZING OR THE COLLECTION OF CONDENSATION THEREON. IF IN DOUBT, CONTACT THE ENGINEER.
- G. ADVISE THE ENGINEER OF ANY CONFLICTS, ERRORS, OMISSIONS, ETC. AT LEAST TEN DAYS PRIOR TO BID DATE. TO ALLOW CLARIFICATION BY WRITTEN ADDENDUM.
- H. WHERE CONFLICTS ARE FOUND BETWEEN DRAWINGS, DETAILS, OR SPECIFICATIONS, THE MORE STRINGENT REQUIREMENT SHALL APPLY. NOTIFY ARCHITECT OF DISCREPANCY IN WRITING.
- I. DEVIATION FROM SPECIFICATIONS OR PLANS REQUIRES PRIOR WRITTEN APPROVAL FROM THE ENGINEERS AND MUST BE SUBMITTED IN WRITING NO LATER THAN TEN DAYS PRIOR TO THE BID DATE.
- J. OBSERVE ALL APPLICABLE CODES, RULES AND REGULATIONS THAT MAY APPLY TO THE WORK UNDER THIS CONTRACT. (CITY, COUNTY, LOCAL, STATE, FEDERAL, MUNICIPALITY, UTILITY COMPANY, OSHA, ETC.)
- K. MOUNTING HEIGHTS FOR WALL MOUNTED DEVICES INDICATED ABOVE FINISHED FLOOR ARE TO CENTER OF DEVICE UNO. MOUNTING HEIGHTS TO CEILING SUSPENDED DEVICES ARE TO BOTTOM OF DEVICE UNO.
- L. INSTALL EQUIPMENT, MATERIALS, ETC. IN STRICT ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS AND DIRECTIONS. IF IN CONFLICT WITH THE DESIGN INDICATED IN CONTRACT DOCUMENTS, ADVISE THE ENGINEER PRIOR TO INSTALLATION FOR CLARIFICATION.
- M. DO NOT REDRESS PANELBOARD TUBS OR OTHER FLUSH-MOUNTED EQUIPMENT IN WALLS THAT HAVE A FIRE RATING. NO INSTALLATION SHALL DIMINISH OR VOID FIRE RESISTIVE RATINGS IN ANYWAY.
- N. THE PURPOSE AND INTENT OF ALL OF THE DOCUMENTS PERTAINING TO THIS PROJECT IS TO PROVIDE A COMPLETE, FUNCTIONAL, SAFE, LIKE-NEW FACILITY. ANYTHING LESS SHALL BE UNACCEPTABLE.
- O. ALL SYSTEMS, EQUIPMENT AND MATERIALS ARE TO BE INSTALLED IN A NEAT AND WORKMANLIKE MANNER. WORK NOT MEETING THIS CRITERION SHALL BE REMOVED AND REINSTALLED SATISFACTORILY. FINAL DETERMINATION OF THE ACCEPTABILITY OF THE QUALITY OF WORK RESIDES WITH THE ENGINEER.
- P. ALL WORK, MATERIALS, EQUIPMENT, ETC. SHALL BE FULLY GUARANTEED FOR ONE FULL CALENDAR YEAR FROM THE DATE OF SUBSTANTIAL COMPLETION AS DOCUMENTED BY THE ENGINEER, UNLESS LONGER WARRANTY PERIODS FOR EQUIPMENT ARE SPECIFIED.
- Q. THE CONTRACTOR IS RESPONSIBLE FOR ALL UTILITY COMPANY FEES, CASH CONTRIBUTIONS OR OTHER COSTS THAT THE UTILITY COMPANY MAY REQUIRE TO COMPLETE THEIR WORK. (ELECTRIC, TELEPHONE, TELEVISION, DATA, ETC.)
- R. ANY VIBRATING, OSCILLATING OR OTHER NOISE OR MOTION PRODUCING EQUIPMENT SHALL BE ISOLATED FROM SURROUNDING SYSTEMS IN AN APPROVED MANNER. NOISE OR STRUCTURALLY DAMAGING INSTALLATIONS SHALL BE SATISFACTORILY REPLACED OR REPAIRED AT THE INSTALLING CONTRACTOR'S EXPENSE. THE FINAL DECISION ON THE SUITABILITY OF A PARTICULAR INSTALLATION'S ACCEPTABILITY SHALL BE THAT OF THE ENGINEER.
- S. CHECK ALL THREE PHASE MOTORS WITH A PHASE ROTATION METER, PRIOR TO PLACING IN SERVICE.
- T. PROVIDE DETAILED SHOP DRAWINGS TO ENGINEER PRIOR TO PURCHASING OR INSTALLING ANY EQUIPMENT.
- U. DEVIATIONS IN SIZES, CAPACITIES, FIT, FINISH, ETC. FOR EQUIPMENT FROM THAT PRIME SPECIFIED SHALL BE THE RESPONSIBILITY OF THE PURCHASER. IF THAT EQUIPMENT, ANY PROVISIONS REQUIRED TO ACCOMMODATE A DEVIATION, WHETHER APPROVED BY THE ENGINEER OR NOT, SHALL BE THE RESPONSIBILITY OF THE PURCHASER.
- V. THE CONSTRUCTION MANAGER, GENERAL CONTRACTOR, OR WHOMEVER HOLDS THE PRIME CONTRACT(S) FOR THIS CONSTRUCTION IS RESPONSIBLE FOR THE COORDINATION, APPEARANCE, SCHEDULING AND TIMELINESS OF THE WORK OF ALL TRADES, CONTRACTORS, SUPPLIERS, INSTALLERS, ETC. POOR OR UNTIMELY WORK ON THE PART OF ANY SUBCONTRACTOR SHALL BE RESOLVED BY THE PARTY WHO ENGAGED THEM ON THIS PROJECT.
- W. WHERE MOUNTING HEIGHTS ARE NOT INDICATED OR ARE IN CONFLICT WITH ANY OTHER BUILDING SYSTEM, CONTACT THE ENGINEER BEFORE AFFECTING INSTALLATION. REFER ALSO TO ARCHITECTURAL INTERIOR AND EXTERIOR ELEVATIONS, CEILING HEIGHTS AND OTHER DETAILS OF THESE DOCUMENTS, AS APPLICABLE.
- X. WHERE FIRE-RATED CEILING ASSEMBLIES ARE NOTED, PROVIDE LISTED FIRE-RATED GYPSUM BOARD OR PRE-MANUFACTURED ENCLOSURES ABOVE LUMINAIRES, CEILING DEVICES, ETC. IN OR ON CEILING, AS REQUIRED TO MAINTAIN CEILING RATINGS.
- Y. COORDINATE THE LOCATION OF DRAINS, ELECTRICAL OUTLETS, GAS OUTLETS, ETC. WITH ALL CASEWORK, KITCHEN EQUIPMENT, MECHANICAL ROOM EQUIPMENT, ETC. PRIOR TO COMMENCING INSTALLATION. WORK NOT SO COORDINATED SHALL BE REMOVED AND PROPERLY INSTALLED AT THE EXPENSE OF THE RESPONSIBLE CONTRACTOR(S).
- Z. ALL ELECTRICAL COMPONENTS OR EQUIPMENT SHALL BE LISTED AND LABELED BY UNDERWRITER'S LABORATORIES OR OTHER APPROVED LISTING AGENCY. APPROVAL AND LABELING OF INDIVIDUAL COMPONENTS ON AN ASSEMBLY IS NOT ACCEPTABLE AS MEETING THIS REQUIREMENT, UNLESS WAIVED BY THE ENGINEER IN WRITING.
- AA. ALL WIRING SYSTEMS SHALL BE INSTALLED WITH A MINIMUM OF SPLICES, CONDUCTORS, WHETHER SINGLE OR MULTIPAIR, SHALL BE INSTALLED CONTINUOUS INsofar AS POSSIBLE FROM TERMINAL POINT TO TERMINAL POINT.
- BB. NO CONDUIT, SUPPORTS, ETC. SHALL BE RUN THROUGH ACCESS CLEARANCES OF EQUIPMENT BY OTHER TRADES (I.E. JAY BOXES). COORDINATE WITH ALL TRADES PRIOR TO CONSTRUCTION.
- CC. ALL CONTRACTORS SHALL EXERCISE EXTREME CARE IN THE COURSE OF THEIR WORK SO AS TO ENSURE THAT THEY DO NOT INTERRUPT ANY EXISTING SERVICE OR SUB-SERVICE FOR SAFETY PURPOSES. PAY PARTICULAR ATTENTION TO THIS PRECAUTION RELATIVE TO NATURAL GAS AND ELECTRICAL LINES. VERIFY THE LOCATION, SIZE, TYPE, ETC. OF EACH UNDERGROUND OR OVERHEAD UTILITY. ALL WORK SHALL BE PERFORMED IN ACCORDANCE WITH ALL FEDERAL, STATE AND/OR LOCAL RULES, REGULATIONS, STANDARD AND SAFETY REQUIREMENTS. UTILITIES SHALL BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE MUNICIPALITY OR UTILITY COMPANY STANDARDS. IN ALL CASES, THE MOST STRINGENT REQUIREMENT SHALL APPLY.
- DD. ALL SUPPORTS FOR EQUIPMENT, DEVICES OR FIXTURES SHALL BE UNIQUE, DIRECTLY FROM THE BUILDING STRUCTURE. DO NOT SUPPORT WORK FROM OTHER TRADES EQUIPMENT OR SUPPORTS WITHOUT WRITTEN PERMISSION FROM THE ENGINEER AND CONSENT OF THE OTHER TRADE, IN WRITING.
- EE. WHERE INTERRUPTING AN EXISTING UTILITY OR SERVICE DELIBERATELY OR ACCIDENTALLY, THE RESPONSIBLE CONTRACTOR SHALL WORK CONTINUOUSLY AS NEEDED TO RESTORE SAME, PROVIDING PREMIUM TIME AS NEEDED.
- FF. THIS CONTRACTOR SHALL BE RESPONSIBLE FOR ALL CUTTING AND PATCHING REQUIRED FOR HIS WORK. ALL CUTTING AND PATCHING SHALL BE IN ACCORDANCE WITH THE ARCHITECT'S STANDARDS FOR SUCH WORK.
- GG. ALL WORK SHALL BE CONCEALED UNLESS SPECIFICALLY INDICATED TO BE EXPOSED, OR REQUIRED TO BE EXPOSED. IF IN DOUBT, CONTACT THE ENGINEER FOR CLARIFICATIONS PRIOR TO INSTALLING ANY SUCH WORK.
- HH. INTERRUPTION OF ANY EXISTING SERVICES SHALL BE COORDINATED WITH THE OWNER, GENERAL CONTRACTOR, UTILITY COMPANY AS NECESSARY, AND THE ARCHITECT, AT LEAST TWO WEEKS IN ADVANCE OF ANTICIPATED INTERRUPTION. A SCHEDULE FOR THESE OUTAGES SHALL BE DEVELOPED AND AGREED UPON BETWEEN THE PARTIES MENTIONED TO AVOID UNNECESSARY INCONVENIENCE TO THE OWNER OR ANY AFFECTED PARTY. NOTIFY THE UTILITY COMPANY OF ANY ANTICIPATED SERVICES REQUIRED TWO WEEKS IN ADVANCE, IN WRITING. IF UTILITY COMPANY REQUIRES A LONGER NOTIFICATION PERIOD, SO PROVIDE.
- II. WHERE BACKBOXES ARE LOCATED IN THE SAME VERTICAL CHANNEL/STUD SPACE ON OPPOSITE SIDES OF THE SAME WALL, PROVIDE SOUND-INSULATING PUTTY AROUND BOXES AS REQUIRED TO ELIMINATE SOUND TRANSMISSION FROM ROOM TO ROOM.
- JJ. JUNCTION BOXES LOCATED ABOVE ACCESSIBLE CEILINGS SHALL BE LOCATED NO MORE THAN 36" ABOVE CEILING LEVEL. LABEL EACH BOX IN AREA OF WORK WITH A PERMANENT MARKER OR IN ACCORDANCE WITH SPECIFICATIONS, WHICHEVER IS MORE STRINGENT.
- KK. ALL MATERIALS FURNISHED AND ALL WORK INSTALLED SHALL COMPLY WITH THE CURRENT EDITION OF THE NATIONAL ELECTRICAL CODES, NATIONAL FIRE CODES OF THE NATIONAL FIRE PROTECTION ASSOCIATION, THE REQUIREMENTS OF LOCAL UTILITY COMPANIES, AND WITH THE REQUIREMENTS OF ALL GOVERNMENTAL AGENCIES OR DEPARTMENTS HAVING JURISDICTION. IF ANY CONFLICTS OR DISCREPANCIES OCCUR THE MOST STRINGENT SHALL APPLY.
- LL. DO NOT SCALE FROM DRAWINGS, AS PRINTING DISTORTS SCALE. WORK SHALL BE LAID OUT FROM DIMENSIONED DRAWINGS, OR DIMENSIONS SUPPLIED TO THE CONTRACTOR.
- MM. NOISY WORK, WORK OUTSIDE CONSTRUCTION BARRIERS, WORK IN OCCUPIED AREAS, ETC. SHALL BE PERFORMED AFTER HOURS OR ON WEEKENDS. COORDINATE EXACT SCHEDULING WITH FACILITY PRIOR TO CONSTRUCTION.
- NN. ALL ITEMS HAVING KEYS LOCKS/OPERATORS SHALL HAVE CORED LOCKS/OPERATORS. ALL KEYING SHALL MATCH THE OWNER'S EXISTING KEY-WAYS. COORDINATE EXACT REQUIREMENTS WITH OWNER PRIOR TO CONSTRUCTION.

DESCRIPTION	MOUNTING HEIGHT (TO CENTER OF BOX)	DRAWING SYMBOL
SWITCHES		
LIGHT SWITCH-GENERAL PURPOSE	46"	\$
DIMMER SWITCH	46"	\$ D
THREE-WAY SWITCH	46"	\$ 3
KEYED SWITCH	46"	\$ K
OCCUPANCY OR VACANCY SENSOR SWITCH	46"	\$ OS, \$ VS
LOW VOLTAGE SWITCH	46"	\$ LV, \$ LV8
NON-REVERSING MOTOR STARTER SNAP SWITCH	AS NOTED	\$ M
TIMER SWITCH	46"	\$ T
OCCUPANCY OR VACANCY SENSOR, CEILING MOUNT	CLG	\$ OS
PHOTO-CELL AS NOTED	AS NOTED	\$ CO
EXAM LIGHT SWITCH	46"	\$ X
NIGHT LIGHT SWITCH WITH CONSTANTLY ILLUMINATED HANDLE	46"	\$ N
SURGICAL LIGHT INTENSITY CONTROL	46"	\$ SL
FOUR-WAY SWITCH	46"	\$ 4
LIGHT SWITCH FOR UNDER-CABINET LIGHTS	46"	\$ U
ILLUMINATED HANDLE LIGHT SWITCH (ILLUMINATED WHEN LOAD IS OFF)	46"	\$ IL
PLOT LIGHT SWITCH (ILLUMINATED WHEN LOAD IS ON)	46"	\$ PL
MOMENTARY CONTACT SWITCH	46"	\$ MC
HAND-OFF-AUTO-3 POSITION SWITCH	46"	\$ HOA
EMERGENCY AUTOMATIC TRANSFER SWITCH FOR LIGHTING CONTROLS (REFER TO DETAIL)		\$ EN
POWER OUTLETS		
SIMPLEX RECEPTACLE	1'-6"	\$
DUPLEX RECEPTACLE-SAFETY TYPE, TAMPER-RESISTANT	1'-6"	\$ S
DUPLEX RECEPTACLE	1'-6"	\$
SLASH THROUGH ANY DEVICE INDICATES MOUNTING ABOVE COUNTER/STUD ONLY. PROVIDE 2" ABOVE BACKSPLASH, OR AT 46" WHERE NO COUNTER IS PRESENT		\$ #
FILLED CENTER BAR INDICATES INTEGRAL GROUND FAULT PROTECTION (GFCI)	1'-6"	\$
FILLED OUTER BARS INDICATES INTEGRAL INTEGRAL USB OUTLETS IN ADDITION TO POWER RECEPTACLES	1'-6"	\$
DUPLEX RECEPTACLE, CEILING MOUNTED	CLG	\$
QUADRUPLX RECEPTACLE	1'-6"	\$
JUNCTION BOX, CEILING OR WALL		\$ J
VOLTAGE/1PH RECEPTACLE, AS NOTED	AS NOTED	\$
VOLTAGE/3PH RECEPTACLE, AS NOTED	1'-6"	\$
GROUND FAULT PROTECTED DUPLEX WITH WEATHER-PROOF "W" IN USE TYPE DIE-CAST METAL COVERPLATE WITH LOCKABLE ENCLOSURE AT OUTLET - (SEE SPECIFICATIONS)	2'-2"	\$ WP
DUPLEX FOR ELECTRIC WATER COOLER, PROVIDE REMOTE, READILY ACCESSIBLE GFI DEVICE AT 48" ADJACENT TO WATER COOLER. COORDINATE EXACT LOCATION WITH PLUMBING CONTRACTOR TO CONCEAL OUTLET BEHIND COOLER		\$ EWC
DEAD FRONT GFCI DEVICE, LABEL AND INSTALL IN READILY ACCESSIBLE LOCATION		\$
GANG RECEPTACLE IN COMBINATION WITH SWITCH (PROVIDE DIVIDER IF LIGHTING CIRCUIT IS 277V)	46"	\$ CS
"DOG-HOUSE" TYPE TWIN DUPLEX RECEPTACLE WITH ONE DUPLEX RECEPTACLE ON BOTH SIDES. SS INDICATES SURGE SUPPRESSION TYPE OUTLET(S)	ON CNTR.	\$ DP
		\$ SS
FIRE ALARM		
MAIN CONTROL PANEL CENTRAL PROCESSING UNIT (CPU)	6'-6" TO TOP	\$ FACP
PULL STATION - DOUBLE ACTION	46" TO LEVER	\$ F
AUDIOVISUAL NOTIFICATION APPLIANCE	WALL, CLG	\$ A
AUDIO-ONLY NOTIFICATION APPLIANCE	WALL, CLG	\$ A
VISUAL-ONLY NOTIFICATION APPLIANCE	WALL, CLG	\$ V
PHOTO-ELECTRIC SMOKE DETECTOR	CLG	\$ SD
PROJECTED BEAM SMOKE DETECTOR, EMITTER (BE) AND RECEIVER (BR)		\$ BE, \$ BR
HEAT DETECTOR	CLG	\$ HD
CARBON MONOXIDE DETECT DETECTOR	ABV CLG	\$ CD
DOOR HOLDER - WALL TYPE	WALL	\$ DH
DOOR HOLDER - CLOSURE TYPE	ABV DOOR	\$ DH C
DUCT SMOKE DETECTOR	ABV CLG	\$ DD
CONNECTION TO SPRINKLER TAMPER SWITCH WITH ADDRESSABLE MODULE		\$ FS
REMOTE L.C.D. FIRE ALARM ANNUNCIATOR	54"	\$ FNA
POWER SUPPLY CONTROL FOR AUDIOVISUAL DEVICES	46"	\$ NAC
TRANSPONDER CABINET	46"	\$ TRCN
FIRE ALARM CONTROL EXTENDER		\$ EXT
ISOLATION MODULE	WALL	\$ I
ZONE ADDRESSABLE MODULE		\$ Z
H.V.A.C. SMOKE DAMPER CONNECTION		\$ SM
ADDRESSABLE RELAY MODULE		\$ R
INDICATES VANDAL PROOF POLYCARBONATE COVER, VANDAL PROOF COVERS SHALL BE UL LISTED FOR USE WITH THE SPECIFIC DEVICE THEY ARE PROTECTING		\$ PC
INDICATES CHIME AUDIBLE NOTIFICATION		\$ CH
DEVICE USED FOR ELEVATOR CONTROL		\$ EL
KEYED, LOCKED PULL STATION - DOUBLE ACTION STATION SHALL ONLY BE OPERABLE VIA KEY IN POSSESSION OF STAFF.	46" TO LEVER	\$ F K
BELL / LIGHT	80"	\$ BL
BELL ONLY	80"	\$ B
PHOTO-ELECTRIC SMOKE DETECTOR FOR PATIENT ROOM MONITORING (SEE RISER)	CLG	\$ SD P
CARBON MONOXIDE ALARM, SINGLE STATION W/SOUNDER BASE	CLG	\$ CM
CARBON MONOXIDE AUDIOVISUAL NOTIFICATION APPLIANCE	WALL	\$ F K AM
POST INDICATOR VALVE		\$ PIV
GRAPHICS DISPLAY TERMINAL		\$ GDT
FLUSH MOUNTED REMOTE ALARM INDICATING STATION/TEST SWITCH	7'-6"	\$ RI
FIREMAN'S PHONE JACK	4'-6"	\$ FP
FIREMAN'S KNOX BOX CONNECTION		\$ KB

DESCRIPTION	MOUNTING HEIGHT (TO CENTER OF BOX)	DRAWING SYMBOL
LIGHTING		
REFER TO LUMINAIRE SCHEDULE FOR EXACT FIXTURE SPECIFICATIONS, MOUNTING HEIGHTS, ETC.		
SURFACE OR SUSPENDED CEILING FIXTURE (SLASH INDICATES RECESSED)		\$
POLE MOUNTED AREA LIGHT		\$
WALL MOUNT FIXTURE		\$
FLOODLIGHT		\$
EXIT LIGHT (CEILING, END, WALL MOUNT)		\$
STRIP FIXTURE		\$
CROSSBARS INDICATES LIGHT IS POWERED FROM THE EMERGENCY-CRITICAL CIRCUIT		\$
PARALLEL HATCHING INDICATES LIGHT IS POWERED FROM THE EMERGENCY/LIFE SAFETY BRANCH		\$
EMERGENCY BATTERY WALL-PACK		\$
SURGICAL/EXAM LIGHT		\$
MISCELLANEOUS		
CONDUIT CONCEALED IN WALLS OR IN CEILING SPACE, ARROWS INDICATE HOME RUN & 4" OF CIRCUITS. HASHMARKS INDICATE # OF CONDUCTORS. DASHED LINE INDICATES CONDUIT BELOW FLOOR.		\$
DISCONNECT SWITCH	5'-0"	\$
MAGNETIC STARTER	5'-0"	\$
MAGNETIC COMBINATION STARTER	5'-0"	\$
VARIABLE FREQUENCY DRIVE	5'-0"	\$
ENCLOSED FLUSH MTD. CIRCUIT BREAKER	5'-0"	\$
PUSHBUTTON STATION	46"	\$
FLEXIBLE CONDUIT	6'-6" TO TOP	\$
PANELBOARD, SURFACE OR FLUSH MOUNTED, HATCHING INDICATES EMERGENCY TRANSFORMER	AS NOTED	\$
EQUIPMENT TAG, REFER TO EQUIPMENT SCHEDULE		\$ EQUIP-1
TAGGED NOTE		\$
REVISION TAG		\$
MECHANICAL EQUIPMENT DESIGNATOR (SEE MECH. SCHEDULES)		\$
WIRE BASKET CABLE TRAY, SIZE AS NOTED	AS SHOWN	\$
LADDER CABLE TRAY, SIZE AS NOTED	AS SHOWN	\$
SOLID BOTTOM CABLE TRAY, SIZE AS NOTED	AS SHOWN	\$
LOW VOLTAGE CABLE PATH		\$
EQUIPMENT HARDWARE CONNECTION (SEE DETAIL)		\$
MOTOR CONNECTION, REFER TO EQUIPMENT CONNECTION SCHEDULE		\$
WIREGUARD - PROVIDE MANUFACTURER'S WEATHERPROOF - NEMA-3R, WET LOCATION LISTED. PROVIDE COVERS, RATINGS, ETC. AS SUITABLE FOR OUTDOORS.		\$ WG
INDICATES EMERGENCY POWER		\$ E.M
GENERATOR ANNUNCIATOR PANEL - SEE SPECIFICATIONS	46"	\$ GEN-A
THERMOSTAT PROVIDED BY MECHANICAL CONTRACTOR, ELECTRICAL CONTRACTOR SHALL PROVIDE BACK-BOX CONDUIT. REFER TO MECHANICAL DRAWINGS FOR LOCATIONS.		\$
CONDUIT UP		\$
CONDUIT DOWN		\$
GROUND BUS BAR ON INSULATED STANDOFFS	2'-0"	\$
BOX ON ANY DEVICE INDICATES SURFACE MOUNTED BACKBOX/WIREMOLD		\$
CIRCLE ON ANY DEVICE INDICATES DEVICE FED FROM STUB-UP CONDUIT		\$
WIREWAY WITH REMOVABLE COVER (SIZE AS NOTED)	AS SHOWN	\$
TRENCH DUCT (SIZE AS NOTED)	AS SHOWN	\$
CORRELL PUSHBUTTON STATION, PROVIDE COMPLETE WITH TRANSFORMER MOUNT ABOVE CEILING IN CORRIDOR NEAR PUSH-BUTTON) AND ALL ACCESSORIES. POWER FROM NEAREST AVAILABLE 120V NORMAL POWER GENERAL RECEPTACLE CIRCUIT, NUTONE OR EQUIVA.	46"	\$ DB
DOORBELL AUDIOVISUAL STATION, PROVIDE CONNECTION TO PUSHBUTTON STATION IN AREA. COORDINATE EXACT AUDIO SOUND (CHIME, BUZZER, ETC.) DESIRED WITH OWNER/ARCHITECT, NUTONE OR EQUIVA.	7'-6"	\$ DB
KITCHEN EQUIPMENT OUTLET COUPLING CONNECTION (SEE DETAIL)		\$ K
INDICATES MOUNTING ABOVE COUNTER-TOP, 2" ABOVE BACKSPLASH, NO HIGHER THAN 48"		\$
EXPLOSION PROOF - PROVIDE WIRING METHODS, ENCLOSURES, RATINGS, ETC. AS SUITABLE FOR HAZARDOUS LOCATION.		\$ XP
PLUMBING FIXTURE SOLENOID VALVE-ELECTRIC EYE SENSOR CONNECTION. COORDINATE EXACT CONNECTION REQUIREMENTS WITH MANUFACTURER.		\$
PLUMBING FIXTURE ELECTRIC EYE TRANSFORMER CONNECTION. TRANSFORMER SHALL BE 120V-24V. MOUNT ABOVE SUSPENDED ACCESSIBLE CEILING IN J-BOX. PROVIDE ADDITIONAL TRANSFORMERS OF SAME TYPE AS IF NEEDED.		\$
PROVIDE CONNECTION TO HAND DRYER (SEE ARCHITECTURAL SPECIFICATIONS)		\$
SURGE PROTECTION DEVICE		\$ SPD
BUS DUCT, AMPERAGES AS NOTED	AS SHOWN	\$
SPECIAL OUTLETS		
FLOORBOX, POWER ONLY, AS SCHEDULED	FLOOR	\$
FLOORBOX, COMBINATION POWER AND LOW VOLTAGE, REFER TO FLOORBOX SCHEDULE	FLOOR	\$
FIRE RATED FLOOR TROUGH FLOOR BOX, COORDINATE EXACT COVER REQUIREMENTS WITH ARCHITECTURAL FINISHER, DEVICES AS SCHEDULED	FLOOR	\$
AUDIOVISUAL SYSTEM OUTLET WITH DUPLEX RECEPTACLE, REFER TO ASSOCIATED DETAIL FOR ADDITIONAL INFORMATION	1'-6"	\$ AV
COMBINATION POWER AND DATA OUTLET LOCATION, REFER TO ASSOCIATED DETAIL FOR ADDITIONAL INFORMATION	1'-6"	\$
COMBINATION POWER AND DATA OUTLET LOCATION, GFCI DUPLEX RECEPTACLE, PROVIDE DUPLEX RECEPTACLE, ONE DATA, HOW, 3.5mm AUDIO, AND VGA OUTLET ON (3) PLATES	1'-6"	\$
SPECIAL VIDEO SYSTEM SIGNAL INPUT		\$
SURFACE PLUG/MOLD		\$
SURFACE WIRE-MOLD		\$
POWER POLE AS NOTED		\$

DESCRIPTION	MOUNTING HEIGHT (TO CENTER OF BOX)	DRAWING SYMBOL
ABBREVIATIONS		
UNLESS OTHERWISE NOTED		
OWNER FURNISHED CONTRACTOR INSTALLED		UON
OWNER FURNISHED, OWNER INSTALLED		OFCI
CONTRACTOR FURNISHED CONTRACTOR INSTALLED		CFCI
CONTRACTOR FURNISHED CONTRACTOR INSTALLED		CFCI
INDICATES EMERGENCY POWER		EM
DATA / VOICE		
DATA OUTLET - NUMBER BESIDE OUTLET INDICATES NUMBER OF DATA JACKS	1'-6"	\$ ID
VOICE OUTLET - NUMBER BESIDE OUTLET INDICATES NUMBER OF DATA VOICE JACKS	1'-6"	\$ ID
COMBINATION OUTLET - NUMBER BESIDE OUTLET INDICATES NUMBER OF DATA VOICE JACKS	1'-6"	\$ ID#V
MAIN DISTRIBUTION FRAME - REFERENCE DATA SYSTEM SCHEMATICS AND DETAILS FOR ADDITIONAL REQUIREMENTS		\$ MDF
INTERMEDIATE DISTRIBUTION FRAME - REFERENCE DATA SYSTEM SCHEMATICS AND DETAILS FOR ADDITIONAL REQUIREMENTS		\$ IDF
WIRELESS ACCESS POINT WITH PROVISIONS FOR (1) DATA OUTLET FOR ANTENNA. PROVIDE A COMPLETE DATA OUTLET WITH FACEPLATE ABOVE CEILING. MOUNTED AT AN ACCESSIBLE HEIGHT NO MORE THAN 24" ABOVE CEILING. AT EACH OUTLET, PROVIDE A 20' COIL OF CABLE AHEAD OF THE OUTLET FOR ADJUSTMENT OF FINAL OUTLET LOCATION. THE CONTRACTOR SHALL COORDINATE EXACT LOCATIONS WITH THE OWNER AND ADJUST OUTLET LOCATIONS AT SUBSTANTIAL COMPLETION TO ACCOMMODATE OWNERS' WAP LOCATIONS. WAPS ARE OWNER-FURNISHED, OWNER-INSTALLED		\$ WAP
RF TRACKER ANTENNA	CLG	\$
TELEMETRY ANTENNA	CLG	\$
OUTLET (VOICE ONLY): PAYPHONE TYPE	AS REQD.	\$ PAY
TELECOMMUNICATIONS SYSTEM BACKBOARD, PROVIDE 80W x 34"D FIRE-RETARDANT PLYWOOD BACKBOARD WITH TWO (2) COATS OF NON-CONDUCTIVE, FIRE-RETARDANT LIGHT GRAY PAINT. # 30 TO GROUND BAR AT MAIN SERVICE SWITCHBOARD, 30"PT GROUND BAR AND A 8'-0", #3 AWG PITGAL AT BACKBOARD. INSTALL BOARD AT 2' AFF. LENGTH OF BOARD AS INDICATED ON FLOOR PLAN)		\$ TEL

Sheet List - Electrical	
SHEET #	SHEET NAME
E001	ELECTRICAL GENERAL INFORMATION
E002	ELECTRICAL DETAILS
E301	ELECTRICAL ENLARGED PLANS - DEMO
E302	ELECTRICAL ENLARGED PLANS - NEW WORK
E901	ELECTRICAL SINGLE LINE



PROJECT

Greater Columbus Convention Center North Facility Chiller Replacement - 2023-5

400 North High Street Columbus, Ohio 43215

CLIENT

FRANKLIN COUNTY CONVENTION FACILITIES AUTHORITY

400 North High Street, 4th Floor Columbus, Ohio 43215

CONSULTANTS

REGISTRATION

KEYPLAN

ISSUE / REVISION

#	Date	Description
1	10/25/2023	BID SET

PROJECT NUMBER

0CCC23

SHEET TITLE

ELECTRICAL GENERAL INFORMATION

SHEET NUMBER

E001

PROJECT

Greater Columbus Convention
Center North Facility Chiller
Replacement - 2023-5


400 North High Street Columbus, Ohio 43215

CLIENT

FRANKLIN COUNTY
CONVENTION FACILITIES
AUTHORITY

400 North High Street, 4th Floor
Columbus, Ohio 43215

CONSULTANTS



DEVICE MOUNTING DETAIL - GENERAL NOTES:

- WHERE DEVICES OF ANY DISCIPLINE ARE LOCATED IN THE SAME GENERAL AREA ON THE PLANS AND ARE SHOWN TO BE MOUNTED AT A SIMILAR HEIGHT, ALIGN HORIZONTALLY ALONG TOP OF DEVICE BACKBOX (AS SHOWN IN DETAIL AND DESCRIBED IN KEY NOTE #2).
- WHERE DEVICES OF ANY DISCIPLINE ARE LOCATED IN THE SAME GENERAL AREA ON THE PLANS AND ARE SHOWN MOUNTED AT DIFFERENT HEIGHTS, ALIGN VERTICALLY ALONG THE CENTERLINE OF THE DEVICE BACKBOX (AS SHOWN IN DETAIL).
- FOR ANY WALL OTHER THAN PAINTED GYPSUM BOARD OR CMU, DEVICE LOCATIONS MUST BE FIELD APPROVED BY ENGINEER OR ARCHITECT PRIOR TO INSTALLATION OF FINISHES.
- ADA REQUIRES 48" ABOVE FINISH FLOOR FOR FRONT ACCESS. SIDE REACH ACCESS ALLOWS A MAXIMUM OF 54" AND A LOW SIDE REACH OF NO LESS THAN 9" ABOVE FINISH FLOOR. ADA FRONT AND SIDE REACH ACCESS MUST BE MAINTAINED FOR NEW AND EXISTING CONSTRUCTION. NOTIFY ARCHITECT AND ENGINEER OF ANY DISCREPANCIES.

DEVICE MOUNTING DETAIL - KEY NOTES:


- MOUNT VISUAL NOTIFICATION APPLIANCES SO THAT ENTIRE LENS IS BETWEEN 80" AND 96" AFF. IF CEILING IS TOO LOW FOR DEVICE TO BE MOUNTED ABOVE 80", MOUNT SO THAT THE LENS IS WITHIN 6" OF FINISHED CEILING.
- ALIGN BACKBOXES OF DEVICES AT THE MOUNTING HEIGHT INDICATED. MEASURE TO THE CENTER OF THE BACKBOX FOR STANDARD OUTLET BOXES. NON-STANDARD BACKBOXES ARE TO BE INSTALLED SUCH THAT THE FINISHED DEVICES ARE ALIGNED ALONG THEIR RESPECTIVE CENTERLINES.
- MOUNTING HEIGHTS SHOWN ILLUSTRATE DESIGN INTENT AND ARE TO BE FOLLOWED UNLESS CONTRADICTED BY APPLICABLE CODE. WHERE DEVICES ARE SHOWN ADJACENT TO DOOR FRAMES ON PLANS INSTALL 12" FROM FRAME TO AVOID SLUSHED SECTIONS OR BRACING. SPECIFIC DEVICES ARE SHOWN IN RELATIVE ORDER FROM DOOR FRAME: WHERE THESE DEVICES ARE NOT PRESENT AT A PARTICULAR LOCATION, ADJUST LOCATIONS CLOSER TO DOOR ACCORDINGLY.
- THE CONTRACTOR IS TO COORDINATE ALL ROUGH-INS WITH ANY COUNTERTOPS/BACKSPLASHES/WALL PROTECTION TO AVOID CONFLICT. ALIGN DEVICE BACKBOXES IN THE BOTTOM OF THE NEXT FULL BLOCK ABOVE THE BACKSPLASH AS SHOWN. FOR NON-BLOCK WALLS ALIGN BOTTOM OF DEVICE BACKBOXES 2" ABOVE BACKSPLASH. COORDINATE WORK WITH CASEWORK AND KITCHEN SHOP DRAWINGS ACCORDINGLY. IF CONFLICT STILL ARISES CONTACT THE ENGINEER FOR DIRECTION ON HOW TO PROCEED.

1 TYPICAL WALL DEVICE MOUNTING DETAIL

SCALE: NONE


2 CONDUIT WALL SLEEVE INSTALLATION

SCALE: NONE




CONDUIT WALL SLEEVE INSTALLATION (EZ PATH)

SCALE: NONE



GENERAL NOTES:

- PROVIDE ONE 2" SPARE CONDUIT SLEEVE THROUGH ALL FULL HEIGHT PARTITIONS FOR FUTURE USE. LABEL AS SPARE FOR OWNER'S USE ONLY. REFER TO ARCHITECTURAL PLANS FOR FULL HEIGHT PARTITION LOCATIONS. USE AT ALL "OPEN" TYPE CABLING PENETRATIONS THROUGH WALLS, FLOORS, ETC.
- PROVIDE CAULKING-STYLE FIRESTOPPING BETWEEN SLEEVE AND WALL MATERIAL TO ANCHOR SLEEVE AND RESTORE RATING OF WALL PER LOCAL AUTH. HAVING JURISDICTION.



GENERAL NOTES:

- NORMAL POWER LABELS SHALL BE BLACK WITH WHITE LETTERS.
- EMERGENCY POWER LABELS SHALL BE RED WITH WHITE LETTERS. LABEL SHOULD ALSO INCLUDE THE WORD "EMERGENCY" IN 1/4" LETTERS.
- EMERGENCY POWER LABELS IN HEALTHCARE APPLICATIONS SHOULD INCLUDE SYSTEM SEVERED "LIFE SAFETY", "CRITICAL" OR "EQUIPMENT".
- UTILIZE SCREW-ON TYPE LAMACOID PLATES.
- THIS DETAILS APPLIES TO ALL ELECTRICAL EQUIPMENT INCLUDING PANELS, SWITCHGEAR, DISCONNECTS, TRANSFORMERS, MOTOR STARTERS, VARIABLE FREQUENCY DRIVES (VFD'S), SPECIAL DEVICE PLATES, INVERTER, AND SIMILAR MATERIALS SHALL BE CLEARLY MARKED AS TO THEIR FUNCTION AND USE.

4 ELECTRICAL EQUIPMENT NAMEPLATE


SCALE: NONE

ELEC - EQUIPMENT CONNECTION SCHEDULE

EQUIP ID	DESCRIPTION	DISCONNECT MEANS	VOLTAGE	POLES	HP	POWER (KVA)	MCA
CH-N1	CHILLER 1	UNIT PROVIDED WITH A REMOTE DRIVE. REFER TO NEW WORK PLANS FOR DRIVE LOCATION. E.C. SHALL WIRE AND INSTALL REMOTE DRIVE.	480	3	N/A	911.80	1610
CH-N2	CHILLER 2	UNIT PROVIDED WITH A REMOTE DRIVE. REFER TO NEW WORK PLANS FOR DRIVE LOCATION. E.C. SHALL WIRE AND INSTALL REMOTE DRIVE.	480	3	N/A	911.80	1610
CH-N3	CHILLER 3	UNIT PROVIDED WITH A EQUIPMENT MOUNTED DRIVE. REFER TO NEW WORK PLANS FOR DRIVE LOCATION. E.C. SHALL WIRE AND INSTALL FREQUENCY DRIVE.	480	3	N/A	476.70	793
CHP-N1	PRIMARY PUMP 1	UNIT PROVIDED WITH A VARIABLE FREQUENCY DRIVE (VFD). E.C. SHALL WIRE AND INSTALL VFD.	480	3	100	103.09	124
CHP-N2	PRIMARY PUMP 2	UNIT PROVIDED WITH A VARIABLE FREQUENCY DRIVE (VFD). E.C. SHALL WIRE AND INSTALL VFD.	480	3	100	103.09	124
CHP-N3	PRIMARY PUMP 3	UNIT PROVIDED WITH A VARIABLE FREQUENCY DRIVE (VFD). E.C. SHALL WIRE AND INSTALL VFD.	480	3	100	103.09	124
CHP-N4	PRIMARY PUMP 4	UNIT PROVIDED WITH A VARIABLE FREQUENCY DRIVE (VFD). E.C. SHALL WIRE AND INSTALL VFD.	480	3	50	54.04	65
CHP-N5	PRIMARY PUMP 5	UNIT PROVIDED WITH A VARIABLE FREQUENCY DRIVE (VFD). E.C. SHALL WIRE AND INSTALL VFD.	480	3	50	54.04	65
CWP-N1	CONDENSER PUMP 1	UNIT PROVIDED WITH A VARIABLE FREQUENCY DRIVE (VFD). E.C. SHALL WIRE AND INSTALL VFD.	480	3	125	129.70	156
CWP-N2	CONDENSER PUMP 2	UNIT PROVIDED WITH A VARIABLE FREQUENCY DRIVE (VFD). E.C. SHALL WIRE AND INSTALL VFD.	480	3	125	129.70	156
CWP-N3	CONDENSER PUMP 3	UNIT PROVIDED WITH A VARIABLE FREQUENCY DRIVE (VFD). E.C. SHALL WIRE AND INSTALL VFD.	480	3	125	129.70	156
CWP-N4	CONDENSER PUMP 4	UNIT PROVIDED WITH A VARIABLE FREQUENCY DRIVE (VFD). E.C. SHALL WIRE AND INSTALL VFD.	480	3	100	103.09	124

REGISTRATION

KEYPLAN



ISSUE / REVISION

#	Date	Description
1	10/25/2023	BID SET

PROJECT NUMBER

OCCC23


SHEET TITLE

ELECTRICAL DETAILS


SHEET NUMBER

E002

Autodesk Docs | Greater Columbus Convention Center RFP Registration | OCC23 | ELEC - R32-14
10/25/2023 10:01:01 AM



2 NORTH BUILDING MEZZ - MECH RM
ELECTRICAL DEMO
SCALE: 1/4" = 1'-0"



1 NORTH BUILDING LEVEL 1 - MECH RM
ELECTRICAL DEMO
SCALE: 1/4" = 1'-0"

KEYNOTES	#
D1 DISCONNECT/REMOVE EXISTING "CP-1" AND RECONNECT TO NEW "CWP-N1". UTILIZE EXISTING ELECTRICAL FEEDER, CONDUIT, AND CIRCUITING. EXTEND EXISTING FEEDER AS NEEDED. CONDUIT AND CONDUCTORS SHALL MATCH EXISTING SIZE AND QUANTITY.	
D2 DISCONNECT/REMOVE EXISTING "CP-2" AND RECONNECT TO NEW "CWP-N2". UTILIZE EXISTING ELECTRICAL FEEDER, CONDUIT, AND CIRCUITING. EXTEND EXISTING FEEDER AS NEEDED. CONDUIT AND CONDUCTORS SHALL MATCH EXISTING SIZE AND QUANTITY.	
D3 DISCONNECT/REMOVE EXISTING "CP-3" AND RECONNECT TO NEW "CWP-N3". UTILIZE EXISTING ELECTRICAL FEEDER, CONDUIT, AND CIRCUITING. EXTEND EXISTING FEEDER AS NEEDED. CONDUIT AND CONDUCTORS SHALL MATCH EXISTING SIZE AND QUANTITY.	
D4 DISCONNECT/REMOVE EXISTING "CP-4" AND RECONNECT TO NEW "CWP-N4". UTILIZE EXISTING ELECTRICAL FEEDER, CONDUIT, AND CIRCUITING. EXTEND EXISTING FEEDER AS NEEDED. CONDUIT AND CONDUCTORS SHALL MATCH EXISTING SIZE AND QUANTITY.	
D5 DISCONNECT/REMOVE EXISTING "CWP-5" AND RECONNECT TO NEW "CHP-N5". UTILIZE EXISTING ELECTRICAL FEEDER, CONDUIT, AND CIRCUITING. EXTEND EXISTING FEEDER TO ACCOMMODATE NEW UNIT AS NEEDED. CONDUIT AND CONDUCTORS SHALL MATCH EXISTING SIZE AND QUANTITY.	
D6 DISCONNECT/REMOVE EXISTING "CWP-6" AND RECONNECT TO NEW "CHP-N6". UTILIZE EXISTING ELECTRICAL FEEDER, CONDUIT, AND CIRCUITING. EXTEND EXISTING FEEDER TO ACCOMMODATE NEW UNIT AS NEEDED. CONDUIT AND CONDUCTORS SHALL MATCH EXISTING SIZE AND QUANTITY.	
D7 DISCONNECT/REMOVE EXISTING "CH-1" AND RECONNECT TO NEW "CH-1". REMOVE EXISTING CONDUIT AND FEEDER FROM EXISTING UNIT BACK TO SOURCE. ALL UNDERGROUND CONDUIT SHALL BE ABANDONED IN PLACE AND CAPPED. RE-ROUTE ALL (8) CONDUITS OVER ELECTRICAL GEAR AND CORE INTO 2ND FLOOR MEZZANINE AND ROUTE THROUGH OPENING DOWN TO THE FIRST LEVEL. EXTEND TO NEW DRIVE LOCATION SHOWN ON THE NEW WORK PLANS.	
D8 DISCONNECT/REMOVE EXISTING "CH-2" AND RECONNECT TO NEW "CH-2". REMOVE EXISTING CONDUIT AND FEEDER FROM EXISTING UNIT BACK TO SOURCE. ALL UNDERGROUND CONDUIT SHALL BE ABANDONED IN PLACE AND CAPPED. RE-ROUTE ALL (8) CONDUITS OVER ELECTRICAL GEAR AND CORE INTO 2ND FLOOR MEZZANINE AND ROUTE THROUGH OPENING DOWN TO THE FIRST LEVEL. EXTEND TO NEW DRIVE LOCATION SHOWN ON THE NEW WORK PLANS.	
D9 DISCONNECT/REMOVE EXISTING "CH-3" AND RECONNECT TO NEW "CH-3". INTERCEPT EXISTING PATHWAY LOCATED ON THE FIRST LEVEL AND UTILIZE BACK TO SOURCE.	
D11 ADD ALTERNATE 2: REMOVE ALL EXISTING LIGHTING IN THIS SPACE AND REPLACE WITH NEW. REFER TO NEW WORK PLANS FOR FIXTURE TYPES.	

- ELECTRICAL DEMOLITION NOTES:**
- DOTTED LINES INDICATE ITEMS FOR REMOVAL (UON) AND THIN SOLID LINES INDICATE EXISTING ITEMS TO REMAIN.
 - THE CONTRACTOR SHALL MAINTAIN THE CONTINUITY OF EXISTING CIRCUITS THAT CONTAIN DEVICES OR EQUIPMENT THAT ARE TO REMAIN. WHEN DEMOLITION OF AN ELECTRICAL DEVICE (OR CIRCUIT) IS INDICATED ON THE DRAWINGS, THE CONTRACTOR SHALL ENSURE THAT OTHER DEVICES OR EQUIPMENT "UPSTREAM" OR "DOWNSTREAM" ON THE CIRCUITS SHALL REMAIN IN "PRE-DEMOLITION" WORKING ORDER. "LEFT-OVER" CIRCUIT BREAKERS SHALL REMAIN, BE SWITCHED TO OFF POSITION, AND BE LABELED AS SPARES IN THEIR PANELS. PROVIDE NEW TYPEWRITTEN DIRECTORIES FOR ALL PANELS AFFECTED.
 - LOCATIONS OF DEVICES, CONNECTIONS, ETC., INDICATED ON THIS DRAWING WERE TAKEN FROM VARIOUS SOURCES. THEY ARE DIAGRAMMATIC ONLY AND ARE SUBJECT TO VARIATION FROM EXISTING CONDITIONS. CERTAIN EXISTING ELEMENTS MAY NOT BE INDICATED AT ALL. THE CONTRACTOR PROPOSING TO DO ANY PART OF THE WORK INDICATED HEREON SHALL VISIT THIS SITE AND DETERMINE TO HIS SATISFACTION THAT THEY MAY COMPLETE ALL WORK REQUIRED FOR THE BID WHICH HE PROPOSES.
 - REMOVE ALL ASSOCIATED BACKBOXES, CONDUIT AND CONDUCTORS FOR DEVICES / FIXTURES / ETC. BEING REMOVED (BACK TO SOURCE), WHETHER INDICATED OR NOT (UON). CONTRACTOR SHALL PATCH AND REPAIR ANY EXISTING WALLS, FLOORS OR CEILINGS WHERE DEVICES ARE SHOWN TO BE REMOVED (PATCH AND REPAIR TO RECEIVE NEW FINISHES - SEE ARCHITECTURAL PLANS).
 - COORDINATE DISPOSAL OF ALL FIXTURES, DEVICES, ETC. (INDICATED FOR DEMOLITION) WITH OWNER. TURN OVER ITEMS REMOVED TO OWNER AT THEIR OPTION.
 - COORDINATE WITH OTHER TRADES FOR THE REMOVAL AND/OR RELOCATION OF ELECTRICAL DEVICES AND CONNECTIONS ASSOCIATED WITH THEIR EQUIPMENT.
 - PROVIDE TEMPORARY EMERGENCY EXIT LIGHTS AT CONSTRUCTION BARRIERS AS REQUIRED.
 - CONTRACTOR SHALL PATCH AND REPAIR ALL EXISTING WALLS / CEILINGS AS REQUIRED WHERE DEVICES ARE BEING REMOVED OR INSTALLED.
 - UNUSED/ABANDONED CONDUCTORS DISCOVERED ABOVE ACCESSIBLE CEILINGS SHALL BE REMOVED IN ACCORDANCE WITH NEC REQUIREMENTS.
 - EXISTING ELECTRICAL SYSTEMS IN CONFLICT WITH CONSTRUCTION SHALL BE RELOCATED TO PERMIT INSTALLATION OF DEVICES AND EQUIPMENT SHOWN ON PLANS.
 - CONTRACTOR SHALL SEAL ALL EXISTING AND NEW PENETRATIONS OF BUILDING ENVELOPE (EXTERIOR WALLS, ROOF, ETC.) WATER-TIGHT AND AS APPROVED BY ARCHITECT AND ENGINEER. ROOFING SHALL BE RESTORED BY A LICENSED ROOFING CONTRACTOR BASED ON WRITTEN INSTRUCTIONS AND DETAILS FROM ROOFING MANUFACTURER AS REQUIRED TO MAINTAIN ROOF WARRANTY. REFER TO ARCHITECTURAL AND ENGINEERING PLANS AND SPECIFICATIONS FOR FURTHER REQUIREMENTS.
 - DEVICES INDICATED WITH AN "R" SHALL BE RELOCATED, REMOVE, PROTECT, AND REINSTALL IN NEW LOCATION INDICATED ON NEW WORK PLANS. INTERCEPT AND EXTEND ALL EXISTING CABLING TO NEW LOCATION. CLEAN AND RE-LAMP RELOCATED LUMINAIRES.
 - ALL EXISTING PANELS AFFECTED BY THIS CONTRACTOR'S WORK SHALL BE PROVIDED WITH NEW TYPE-WRITTEN PANEL DIRECTORIES AND INSERT SLEEVES. PANEL DIRECTORIES SHALL NOT USE ROOM NAMES OR NUMBERS FROM THESE DRAWINGS. DIRECTORIES SHALL BE DETAILED AND COORDINATED WITH OWNER'S SUITE NUMBERS, FINAL ROOM NUMBERS, IT RACK NAMES, WORKSTATION DESIGNATIONS, ETC. UNUSED BREAKERS SHALL BE IN OFF POSITION.

PROJECT

**Greater Columbus Convention
Center North Facility Chiller
Replacement - 2023-5**

400 North High Street Columbus, Ohio 43215


CLIENT

**FRANKLIN COUNTY
CONVENTION FACILITIES
AUTHORITY**
400 North High Street, 4th Floor
Columbus, Ohio 43215

CONSULTANTS

REGISTRATION

KEYPLAN



ISSUE / REVISION


#	Date	BID SET	Description
1	10/25/2023	BID SET	

PROJECT NUMBER
OCC23

SHEET TITLE
**ELECTRICAL ENLARGED PLANS -
DEMO**

SHEET NUMBER

Autodesk Docs | Greater Columbus Convention Center RFP Replacement OCC23 | ELEC R32-14
10/25/2023 10:51:01 AM




GENERAL NOTES (POWER):

- REFER TO THE ARCHITECT'S REFLECTED CEILING PLANS, ELEVATIONS, AND CASEWORK DETAILS FOR EXACT LOCATIONS OF ALL WALL AND CEILING MOUNTED ELECTRICAL DEVICES.
- CONTRACTOR SHALL FOLLOW BRANCH CIRCUITING LAY-OUT, AS INDICATED ON THE FLOOR PLANS, WITH A MAXIMUM OF THREE (3) BRANCH CIRCUITS PER HOMERUN. EACH BRANCH CIRCUIT SHALL BE PROVIDED WITH A DEDICATED NEUTRAL CONDUCTOR. DEDICATED NEUTRAL CONDUCTORS SHALL BE CONSIDERED CURRENT CARRYING. IF ADDITIONAL CONDUCTORS ARE RAN IN THE SAME CONDUIT WITH THOSE INDICATED, CONTRACTOR SHALL DERATE ALL CURRENT CARRYING CONDUCTORS PER NEC 310.15(B)(3), AND UPSIZE CONDUIT AS REQUIRED PER NEC 300.17 AND ANNEX C. MULTIWIRE BRANCH CIRCUITS AS DEFINED IN NEC 100/210.4 (CIRCUITS SHARING A COMMON NEUTRAL CONDUCTOR) SHALL NOT BE PERMITTED.
- IDENTIFY THE PANEL AND CIRCUIT NUMBER FOR ALL RECEPTACLES, SWITCHES, ETC. IN AREA OF CONSTRUCTION. PROVIDE CLEAR ADHESIVE LABELS WITH BLACK LETTERING. MARK INSIDES OF ALL DEVICE BOXES WITH PANEL AND CIRCUIT NUMBER.
- LOCATIONS OF ELECTRICAL CONNECTIONS AND LOCAL DISCONNECTS SHALL BE COORDINATED WITH MECHANICAL AND PLUMBING CONTRACTORS TO ENSURE ACCESS AND WORKING CLEARANCE IS MAINTAINED PER NEC. NOTIFY OTHER TRADES OF REQUIRED CLEARANCE AREAS TO AVOID ROUTING OF OTHER SYSTEMS IN THESE AREAS. DO NOT INSTALL ELECTRICAL EQUIPMENT OVER EQUIPMENT NAMEPLATES OR ACCESS PANELS OR THROUGH ACCESS/MAINTENANCE CLEARANCES OF EQUIPMENT BY OTHER TRADES.

KEYNOTES

- | | |
|-----|---|
| E1 | DISCONNECT/REMOVE EXISTING "CDP-1" AND RECONNECT TO NEW "CWP-N1". UTILIZE EXISTING ELECTRICAL FEEDER, CONDUIT, AND CIRCUITING. EXTEND EXISTING FEEDER TO ACCOMMODATE NEW UNIT AS NEEDED. CONDUIT AND CONDUCTORS SHALL MATCH EXISTING SIZE AND QUANTITY. IF ALTERNATE 1 IS ACCEPTED: REMOVE EXISTING FEEDERS BACK TO SOURCE AND CONNECT NEW "CWP-1" TO NEW "SWITCHBOARD 4B". PROVIDE A 225A, 3-POLE CIRCUIT BREAKER IN AVAILABLE SPACE. PROVIDE (3)#4/0 CU AND (1)#4 CU GROUND IN 2.5" CONDUIT FOR ELECTRICAL CONNECTION. |
| E2 | DISCONNECT/REMOVE EXISTING "CDP-2" AND RECONNECT TO NEW "CWP-N2". UTILIZE EXISTING ELECTRICAL FEEDER, CONDUIT, AND CIRCUITING. EXTEND EXISTING FEEDER TO ACCOMMODATE NEW UNIT AS NEEDED. CONDUIT AND CONDUCTORS SHALL MATCH EXISTING SIZE AND QUANTITY. IF ALTERNATE 1 IS ACCEPTED: REMOVE EXISTING FEEDERS BACK TO SOURCE AND CONNECT NEW "CWP-2" TO NEW "SWITCHBOARD 4B". PROVIDE A 225A, 3-POLE CIRCUIT BREAKER IN AVAILABLE SPACE. PROVIDE (3)#4/0 CU AND (1)#4 CU GROUND IN 2.5" CONDUIT FOR ELECTRICAL CONNECTION. |
| E3 | DISCONNECT/REMOVE EXISTING "CDP-3" AND RECONNECT TO NEW "CWP-N3". UTILIZE EXISTING ELECTRICAL FEEDER, CONDUIT, AND CIRCUITING. EXTEND EXISTING FEEDER TO ACCOMMODATE NEW UNIT AS NEEDED. CONDUIT AND CONDUCTORS SHALL MATCH EXISTING SIZE AND QUANTITY. IF ALTERNATE 1 IS ACCEPTED: REMOVE EXISTING FEEDERS BACK TO SOURCE AND CONNECT NEW "CWP-3" TO NEW "SWITCHBOARD 4B". PROVIDE A 225A, 3-POLE CIRCUIT BREAKER IN AVAILABLE SPACE. PROVIDE (3)#4/0 CU AND (1)#4 CU GROUND IN 2.5" CONDUIT FOR ELECTRICAL CONNECTION. |
| E4 | DISCONNECT/REMOVE EXISTING "CDP-4" AND RECONNECT TO NEW "CWP-N4". UTILIZE EXISTING ELECTRICAL FEEDER, CONDUIT, AND CIRCUITING. EXTEND EXISTING FEEDER TO ACCOMMODATE NEW UNIT AS NEEDED. CONDUIT AND CONDUCTORS SHALL MATCH EXISTING SIZE AND QUANTITY. IF ALTERNATE 1 IS ACCEPTED: REMOVE EXISTING FEEDERS BACK TO SOURCE AND CONNECT NEW "CWP-4" TO NEW "SWITCHBOARD 4B". PROVIDE A 200A, 3-POLE CIRCUIT BREAKER IN AVAILABLE SPACE. PROVIDE (3)#3/0 CU AND (1)#6 CU GROUND IN 2" CONDUIT FOR ELECTRICAL CONNECTION. |
| E5 | DISCONNECT/REMOVE EXISTING "CWP-4" AND RECONNECT TO NEW "CHP-N4". UTILIZE EXISTING ELECTRICAL FEEDER, CONDUIT, AND CIRCUITING. EXTEND EXISTING FEEDER TO ACCOMMODATE NEW UNIT AS NEEDED. CONDUIT AND CONDUCTORS SHALL MATCH EXISTING SIZE AND QUANTITY. |
| E6 | DISCONNECT/REMOVE EXISTING "CWP-5" AND RECONNECT TO NEW "CHP-N5". UTILIZE EXISTING ELECTRICAL FEEDER, CONDUIT, AND CIRCUITING. EXTEND EXISTING FEEDER TO ACCOMMODATE NEW UNIT AS NEEDED. CONDUIT AND CONDUCTORS SHALL MATCH EXISTING SIZE AND QUANTITY. |
| E7 | DISCONNECT/REMOVE EXISTING "CH-1" AND RECONNECT TO NEW "CH-1". REMOVE EXISTING CONDUIT AND FEEDER FROM EXISTING UNIT BACK TO SOURCE. ALL UNDERGROUND CONDUIT SHALL BE ABANDONED IN PLACE AND CAPPED. RE-ROUTE ALL (6) CONDUITS OVER ELECTRICAL GEAR AND CORE INTO 2ND FLOOR MEZZANINE AND ROUTE THROUGH OPENING DOWN TO THE FIRST LEVEL. EXTEND TO NEW DRIVE LOCATION SHOWN ON THE NEW WORK PLANS. PROVIDE (6)-500 CU AND (1)#250 CU GROUND IN 3" CONDUIT FOR ELECTRICAL CONNECTION. E.C. SHALL LAYOUT DRIVE LOCATION FOR ENGINEER APPROVAL PRIOR TO ROUNG-IN AND INSTALLATION. |
| E8 | DISCONNECT/REMOVE EXISTING "CH-2" AND RECONNECT TO NEW "CH-2". REMOVE EXISTING CONDUIT AND FEEDER FROM EXISTING UNIT BACK TO SOURCE. ALL UNDERGROUND CONDUIT SHALL BE ABANDONED IN PLACE AND CAPPED. RE-ROUTE ALL (6) CONDUITS OVER ELECTRICAL GEAR AND CORE INTO 2ND FLOOR MEZZANINE AND ROUTE THROUGH OPENING DOWN TO THE FIRST LEVEL. EXTEND TO NEW DRIVE LOCATION SHOWN ON THE NEW WORK PLANS. PROVIDE (6)-500 CU AND (1)#250 CU GROUND IN 3" CONDUIT FOR ELECTRICAL CONNECTION. E.C. SHALL LAYOUT DRIVE LOCATION FOR ENGINEER APPROVAL PRIOR TO ROUNG-IN AND INSTALLATION. |
| E9 | DISCONNECT/REMOVE EXISTING "CH-3" AND RECONNECT TO NEW "CH-3". INTERCEPT EXISTING PATHWAY LOCATED ON THE FIRST LEVEL AND UTILIZE BACK TO SOURCE. REPLACE EXISTING FUSES IN HEAD END FUSED SWITCH IN SWITCHBOARD 4A WITH 800A FUSES. PROVIDE (3)#600 CU AND (1)#1/0 GROUND IN 3.5" CONDUIT FOR ELECTRICAL CONNECTION. |
| E10 | PROVIDE 6" HOUSEKEEPING PAD FOR FLOOR MOUNTED AFD. |
| E11 | PROVIDE UNISTRUT STRUCTURE FOR MOUNTING OF PANELBOARD. PROVIDE 45 DEGREE KICKERS AND ALL OTHER REQUIRED COMPONENTS FOR LATERAL SUPPORT AND COMPLETE SYSTEM. |
| L1 | ADD ALTERNATE 2: REMOVE ALL EXISTING LIGHTING IN THIS SPACE AND REPLACE WITH NEW. MAINTAIN ALL EXISTING CONDUIT, CONDUCTORS, AND CONTROLS. EXTEND FEEDER IF NECESSARY. MAINTAIN EXISTING CONDUIT/CONDUCTOR SIZE AND QUANTITIES. EM1: PROVIDE LITHONIA ELM4L DUAL HEAD EMERGENCY LIGHTING FIXTURE WITH EQUALS HUBBELL, COLUMBIA, DAY-BRITE AND COOPER. CH1: PROVIDE LITHONIA ZL1D L48-SMR-700LM-FST-MVOLF40K-80CRI-WH-ZACVH M100 WITH EQUALS HUBBELL, COLUMBIA, DAY-BRITE AND COOPER. PROVIDE 10W EMERGENCY BATTERY PACK OPTION FOR ALL FIXTURES WITH "EM" DESIGNATION. |



PROJECT

**Greater Columbus Convention
Center North Facility Chiller
Replacement - 2023-5**

400 North High Street Columbus, Ohio 43215

CLIENT


**FRANKLIN COUNTY
CONVENTION FACILITIES
AUTHORITY**

400 North High Street, 4th Floor
Columbus, Ohio 43215

CONSULTANTS

REGISTRATION

KEYPLAN



ISSUE / REVISION

#	Date	BID SET	Description
1	10/25/2023	BID SET	

PROJECT NUMBER

OCCC23

SHEET TITLE

**ELECTRICAL ENLARGED PLANS -
NEW WORK**

SHEET NUMBER

E302

